

CLEANWELL

HIGH PRESSURE CLEANING EQUIPMENT



HS ELECTRIC

STATIC HOT & COLD PRESSURE CLEANERS

- ✓ Performances ranging from 50 bar to 200 bar
- ✓ 400 – 415 Volts. 50 Hz
- ✓ **ADVANTAGES OVER OIL FIRED**
 - No smelly diesel fumes
 - No noise from burner
 - No dirty diesel problems
 - Approx about £1 an hour cheaper to run
 - Very little servicing to be carried out
 - A more environmentally friendly machine
 - More reliable and efficient
- ✓ To prolong the life of the chassis it is constructed of steel which is zintec coated with a polyester finish. Also available in stainless steel
- ✓ Low pressure chemical injection
- ✓ Supplied with 9m. high pressure hose, on/off gun, lance & nozzle
- ✓ Dimensions: Depth 850mm x Width 950mm x Height 1710mm
- ✓ Designed and manufactured by Cleanwell to comply with CE Legislation
- ✓ Environmentally friendly specification
- ✓ 1 Year warranty subject to conditions of sale

- ✓ Stainless steel water tank which holds 300 litres. Heavily insulated to maintain a high water temperature
- ✓ Two high efficiency immersion heaters able to produce heat up to 85°C
- ✓ Visual digital temperature display on dashboard
- ✓ Fitted as standard with 24 volt control, anti leak detection and auto time delayed shut down at zero pressure which has proven to reduce maintenance costs by 75%

British Manufacturer

let Cleanwell handle the pressure

HS ELECTRICALLY HEATED HOT HIGH PRESSURE CLEANERS

THE OMISSION FREE HOT HIGH PRESSURE CLEANER FOR SPECIAL APPLICATIONS

The electrically heated hot water high pressure cleaner with stainless steel tank with float switch isolator for low water and digital temperature gauge. Ideal for applications whenever exhaust from oil fired pressure cleaners are undesirable or prohibited. For example food industry, abattoirs, hospitals and the chemical industry.

PERFORMANCE SPECIFICATIONS

	18 KW	24 KW	36 KW
OPERATING PRESSURE	170 BAR	170 BAR	3000 PSI / 200 BAR
LITRES PER MINUTE	13	13	15
TEMP. OF HEATING BOILER °C	30° - 80°	30° - 80°	30° - 80°
STAINLESS STEEL TANK CAPACITY	53 GALLONS 240 LTRS	53 GALLONS 240 LTRS	53 GALLONS 240 LTRS
CONNECTED LOAD	18 + 4 KW	24 + 4 KW	24 or 36 + 5.5 KW
VOLTS / HZ	415v / 3PH / 50	415v / 3PH / 50	415v / 3PH / 50

ALSO AVAILABLE IN 60Hz OR WITH ATEX APPROVAL ON REQUEST