

CLEANWELL

HIGH PRESSURE CLEANING EQUIPMENT



SS ELECTRIC HOT HIGH PRESSURE CLEANER

- ✓ 13 litres @ 170 bar
- ✓ 400 – 415 Volts
- ✓ Fitted as standard with 24 volt control, anti leak detection and auto time delayed shut down at zero pressure which maintains life of the machine and protects the operator
- ✓ The automatic time delayed shut down has proven to reduce maintenance costs by 75%
- ✓ Supplied with 30ft high pressure hose, on/off gun, lance & nozzle
- ✓ Pressure reducing valve for reducing pressure
- ✓ Long life, slow revving 1400 RPM electric motor and Interpump pump with flexible drive coupling and bell housing
- ✓ The 4 wheeled zintec coated chassis painted black which comes complete with a long life, weather resistant, rust proof stainless steel cover fitted with a stainless steel water tank that's heavily insulated to maintain a high water temperature
- ✓ High pressure chemical injection complete with metering valve
- ✓ Improved high efficiency immersion heaters able to produce heat up to 85 degrees centigrade fitted to a stainless steel water tank with low level shut down
- ✓ Rotary thermostat adjustable from 0-90°C
- ✓ Environmentally friendly specification
- ✓ Designed and manufactured by Cleanwell to comply with CE legislation
- ✓ 1 Year warranty subject to conditions of sale

British Manufacturer

let Cleanwell handle the pressure

SS ELECTRICALLY HEATED HOT HIGH PRESSURE CLEANERS

THE OMISSION FREE HOT HIGH PRESSURE CLEANER FOR SPECIAL APPLICATIONS

The electrically heated hot water high pressure cleaner with stainless steel three chamber water heater – a float tank, heating chamber and a holding tank. Ideal for applications whenever exhaust from oil fired pressure cleaners is undesirable or prohibited. For example food industry, abattoirs, hospitals and the chemical industry.

PERFORMANCE SPECIFICATIONS

	18 KW	24 KW
OPERATING PRESSURE	170 BAR	170 BAR
LITRES PER MINUTE	13	13
TEMP. OF HEATING BOILER °C	30° - 80°	30° - 80°
TANK CAPACITY LTRS	80	80
CONNECTED LOAD	18 + 4 KW	24 + 4 KW
VOLTS / HZ	415v / 3PH / 50	415v / 3PH / 50

ALSO AVAILABLE IN 60HZ AND ZONE 1 FOR FLAME PROOF AREAS.