

# CLEANWELL

## HIGH PRESSURE CLEANING EQUIPMENT



## SS ELECTRIC

### HOT HIGH PRESSURE CLEANER

- ✔ Fitted as standard with 24 volt control, anti leak detection and auto time delayed shut down at zero pressure which maintains the life of the machine and protects the operator
- ✔ The automatic time delayed shut down has proven to reduce maintenance costs by 75%
- ✔ The fuel tank comes complete with triple fuel filter system, low level fuel cut out & instant self bleeding system which is controlled by an electronic fuel pump
- ✔ Supplied with 30ft. high pressure hose, on/off gun, lance & nozzle
- ✔ Long life, slow revving 1400 RPM electric motor direct coupled to an Interpump pump which is able to suck from an outside water tank
- ✔ Performances ranging from 1500 psi 100 bar to 3000 psi 200 bar. Available in all electrical supplies 110v, 240v, 415v. Also available as an electrically heated high pressure
- ✔ The 4 wheeled stove enamelled chassis comes complete with a long life, weather resistant, rust-proof stainless steel cover fitted with a stainless steel water tank which meets the Water Bylaws regulations
- ✔ High pressure chemical injection complete with metering valve
- ✔ Improved high efficiency burner which is able to produce up to 150°C through a steam valve system
- ✔ Environmentally friendly specification
- ✔ Designed and manufactured by Cleanwell to comply with CE Legislation
- ✔ 1 Year guarantee subject to conditions of sale

British Manufacturer

let Cleanwell handle the pressure

# SS ELECTRICALLY HEATED HOT HIGH PRESSURE CLEANERS

## THE OMISSION FREE HOT HIGH PRESSURE CLEANER FOR SPECIAL APPLICATIONS

The electrically heated hot water high pressure cleaner with stainless steel three chamber water heater – a float tank, heating chamber and a holding tank. Ideal for applications whenever exhaust from oil fired pressure cleaners is undesirable or prohibited. For example food industry, abattoirs, hospitals and the chemical industry.

### PERFORMANCE SPECIFICATIONS

	12 KW	18 KW	24 KW	36 KW
OPERATING PRESSURE	170 BAR	170 BAR	170 BAR	3000 PSI / 200 BAR
LITRES PER MINUTE	11	13	13	15
TEMP. OF HEATING BOILER °C	30° - 80°	30° - 80°	30° - 80°	30° - 80°
TANK CAPACITY LTRS	80	80	80	80
CONNECTED LOAD	12 + 4 KW	18 + 4 KW	24 + 4 KW	36 + 5.5 KW
VOLTS / HZ	415/ 3PH / 50	415 / 3PH / 50	415 / 3PH / 50	415 / 3PH / 50

**ALSO AVAILABLE IN 60HZ AND ZONE 1 FOR FLAME PROOF AREAS.**